

## Odyssey Air & Nitrogen Boosters



### SINGLE STAGE

Generally used for boosting 1.3 to 5 times existing pressure

5 to 75 HP

650 to 30,250 SCFH

Up to 300 PSIG

Air cooled (Water cooled available upon request)

### Available Options:

- ✓ Special Sealing Systems
- ✓ High Temp Cooling Fan
- ✓ Modbus TCP/IP Communications
- ✓ Multiple Unit Lead/Lag & Alternate Controls
- ✓ NEMA 4X Control Panel Enclosure
- ✓ Stainless Steel Control Panel Enclosure
- ✓ Cold Weather Package
- ✓ Voltage - 200, 208, 230, 400, 575
- ✓ Moisture Separators
- ✓ Closed Loop Cooling Skid
- ✓ Remote Monitoring
- ✓ Sound Deadening Enclosure



### TWO STAGE

Generally used for boosting 1.3 to 5 times existing pressure

5 to 60 HP

1,270 to 15,120 SCFH


Up to 600 PSIG

Air cooled (Water cooled available upon request)

## Odyssey Air & Nitrogen Boosters

	DS012	DS015	DS026	DS033	DS044	DS060	DS081	DS087	DS133	DS192	DS303	Odyssey Range
HP	5	5	7.5	10-15	10-15	20-25	25-40	20-25	40-75	40-50	50-75	5 - 75
Flow - SCFM	18	25	43	56	74	98	136	146	245	312	504	18 - 504
Pressure - PSIG	600	300	300	500	300	500	600	300	600	300	300	300 - 600

DS012, DS015, DS026



DS033




DS060



DS087



DS133, DS192, DS303



DS044



DS081



11 Base Models